

Analogue (Up to 1kV) Insulation Tester



CE

1131 IN

FEATURES

- High quality Taut Band movement.
- Three insulation test voltages(DC) : 250V, 500V, 1000V.
- Two ranges for continuity test : 2Ω & 20Ω.
- Compact and lightweight.
- AC voltmeter with linear scale up to 600 Vac.
- 200 mA continuity short circuit current.
- 1mA test current on insulation test at nominal voltage.
- Automatic discharge of capacitive and inductive circuit with charge stored in the circuit under test.
- Live warning and display or external voltage presence.
- Fuse, air gap, crowbar and overload protected.
- On line battery monitoring shows if battery is ok.
- Manual zero ohm adjustment.
- Low battery consumption.
- Mirror scale.
- Push and turn locking switch for continuous and hand free testing.
- BS 16th edition.

SPECIFICATIONS

Insulation Resistance

Test voltage (DC V)	250V / 500V / 1000V
---------------------	---------------------

Output voltage on open circuit	Rated test voltage +10%
--------------------------------	-------------------------

Measuring ranges	0-100MΩ / 0-200MΩ / 0-400MΩ
------------------	-----------------------------

Mid-scale value	1MΩ / 2MΩ / 4MΩ
-----------------	-----------------

Scale multiplier	×1/2 / ×1 / ×2
------------------	----------------

Accuracy	± 5% of indicated value
----------	-------------------------

Output short-circuit current	≥ 1.0mA
------------------------------	---------

Continuity

Measuring ranges	2Ω / 20Ω
------------------	----------

zero Ω adjustment by knob	√
---------------------------	---

Output short-circuit current	≥ 200 mA
------------------------------	----------

Accuracy	± 1.5% of scale length
----------	------------------------

AC Voltage

Range	0-600V AC
-------	-----------

Accuracy	± 3% of scale length
----------	----------------------

General

Voltage warning	Warning light circuit live lit From 90Vdc / 70Vac, Buzzer beep from 24V ac/dc
Battery check	Battery check indicate good batteries from 8.5Vdc to 13Vdc during a load test of 250mA.

Battery OK	Battery OK LED lit from 8.5Vdc and is operative while testing.
------------	--

Dimensions	175(L) × 85(W) × 75(D)mm
------------	--------------------------

Weight (battery included)	Approx. 650g
---------------------------	--------------

Power source	1.5V (AA) × 8
--------------	---------------

Safety standard	EN 61010-1 CAT III 600V EN 61326-1
-----------------	---------------------------------------

Accessories	Instruction manual
-------------	--------------------

Accessories	Test leads
Accessories	Shoulder belt
Accessories	Soft pouch
Accessories	Batteries



AL-24-5

CAC-1132

BET-1800