

# 300 Series Clamp Meters




Rugged. Reliable. Accurate.

The new Fluke 302+, 303 and 305 come with all the rugged, reliable and accurate features you have come to trust, in a small, ergonomic design. The innovative body design offers a more compact tool to meet your needs. With features of AC current measurements upto 600 A (303), a large 30 mm jaw opening and CAT IV 300 V/CAT III 600 V safety rating, you get an easy-to-use tool that handles your everyday electrical maintenance needs.



**Features & Benefits:**

- 400 AAC current measurement (302+)
- 600 AAC current Measurement (303)
- 999.9 AAC current Measurement (305)
- Cat IV 300 V/CAT III 600 V safety rated
- 30 mm jaw size for multiple applications
- Resistance range upto 4kΩ
- Slim, ergonomic design is easy to carry and simple to use
- Easy to read backlight display

Specifications				
		302+	303	305
AC Current	Range	400.0 A	600.0 A	999.9 A
	Accuracy	1.8% ± 5	1.8% ± 5	1.8% ± 5
AC voltage	Range	400/600 V	400/600 V	400/600 V
	Accuracy	1.5% ± 5	1.5% ± 5	1.5% ± 5
DC voltage	Range	400/600 V	400/600 V	400/600 V
	Accuracy	1.0% ± 5	1.0% ± 5	1.0% ± 5
Resistance	Range	4000Ω	4000Ω	4000Ω
Continuity		≤70Ω	≤70Ω	≤70Ω
Backlight display		Yes	Yes	Yes
Data hold		Yes	Yes	Yes
Size	H x W x D (mm)	208 x 58.5 x 28	208 x 58.5 x 28	208 x 58.5 x 28
	Jaw size	30mm	30mm	30mm
Safety rating		CAT III 600V/ CAT IV 300V	CAT III 600V/ CAT IV 300V	CAT III 600V/ CAT IV 300V
Screen refresh rate		> 2 times / sec.	> 2 times / sec.	> 2 times / sec.
Test leads		TL75	TL75	TL75
Battery		2 AA batteries	2 AA batteries	2 AA batteries
Warranty		Two years	Two years	Two years