









- To test the material surfaces, such as metal, granite, ceramic, plastic, paper, etc.
- According to ISO 2813, ASTM D2457, ASTM D523
- Memory of 10000 measurement results for browsing and output

■ To test the gloss of coating, such as painting, varnish, printing ink, etc.

Automatic power off



software CD (included)

## connect to mobile phone via bluetooth (only Android system)




## connect to computer via bluetooth or USB cable



## **SPECIFICATION**

OI LOII IOATION			
Incidence angle	20°	60°	85°
Measuring range	0~2000GU	0~1000GU	0~160GU
Resolution	0.1GU (range≤119.9GU)		
	1GU (range>119.9GU)		
Accuracy	±1.5GU (range≤119.9GU)		
	±1.5% (range>119.9GU)		
Repeatability	0.2GU (range≤119.9GU)		
	0.2% (range>119.9GU)		
Zero set error	0.2GU		
Measuring area	10×9mm	16×9mm	39×5mm
Output	USB and bluetooth		
Power supply	1×1.5V AA battery		
Dimension	155×48×75mm		
Weight	400g		



software (included), test can be controlled from the software, display test data, output to Excel

## STANDARD DELIVERY

017111271112 222172111		
Main unit	1 pc	
Base with calibration block	1 pc	
Software and USB cable	1 pc	
Bluetooth receiver	1 pc	