

## YIHUA 1501A DC power supply



Input voltage: 110V/220V/230V/240V Product weight: 1.06kg/pcs

Size: 17\*33\*21CM

## **Product Characteristics**

- 1. Small and convenient body, easy to carry.
- 2. High accuracy and reliability
- 3. Short circuit protection and automatic recovery function
- 4. Adjustable voltage 0 ~ 15V, 0 ~ 1A
- 5. Cost effective, lower price.

## b) Applicable range

Primarily outputs 0-15 V DC and  $0 \sim 1$  A.

The test is more accurate; widely used in the maintenance of mobile phones and oth er relevant industries.

## **Parameters**

Parameters	
Rated voltage	AC220V±10% 50Hz
Power of complete machine	15W
Operating environment	0~40°C relative humidity<80%
Storage temperature	- 20~80°C relative humidity<80%
Dimensions of the machine body	17*33*21CM
Weight	1.06KG
Performance parameters	
Output voltage	Adjustable continuously within $0{\sim}15\text{V}$
Output current	Adjustable continuously within 0~1A
	(current limitation adjustment when above 0.2A)
Output power	15 <b>W</b>
Source effect	≤1mV
Load effect	≤0.33%
Ripple noise	≤3mVrms (5Hz ~ 1MHz) /≤3mArms
Display accuracy	0.1V/0.1A/1mA
Protection mode	Over-current, short circuit, over-
	temperature protection
Dissipation mode	Air cooling

