



## YIHUA 1502DD+ Communication Maintain DC power supply



Input voltage: 110V/220V/230V/240V	Product weight: 1.06kg/pcs
Size: 18*12.8*12.5cm	

### Product Features

1. Dual LED displays to show current and voltage. High-performance mobile phone repair equipment that is both affordable and easy to operate.
2. Able to detect GSM, CDMA, and PHS among other mobile phone

radiofrequency signals.

3. Comes with a 0-15V DC output function (the voltage output can be adjusted both by gears or a slide controller).

## Product Parameter

Parameters	
Rated voltage	AC220V±10% 50Hz
Operating environment	0~40°C relative humidity<80%
Storage temperature	-20~80°C relative humidity<80%
Dimensions of the machine body	17*33*21CM
Weight	1.06KG
Performance parameters	
Output voltage	Adjustable continuously within 0~15V
Output current	Adjustable continuously within 0~1A (current limitation adjustment when above 0.2A)
Output power	15W
Source effect	≤1mV
Load effect	≤0.33%
Ripple noise	≤3mVrms (5Hz ~ 1MHz) / ≤3mArms
Display accuracy	0.1V/0.1A/1mA
Protection mode	Over-current, short circuit, over-temperature protection
Dissipation mode	Air cooling

YIHUA®

