

PCE Americas Inc. 711 Commerce Way Suite 8 Jupiter FL-33458 USA From outside US: +1 Tel: (561) 320-9162 Fax: (561) 320-9176 info@pce-americas.com PCE Instruments UK Ltd. Units 12/13 Southpoint Business Park Ensign way Hampshire / Southampton United Kingdom, SO31 4RF From outside UK: +44 Tel: (0) 2380 98703 0 Fax: (0) 2380 98703 9 info@pce-instruments.com

www.pce-instruments.com/english www.pce-instruments.com

## **Digital multimeter PCE-PI 10**

## Rotary field indicator with voltage tester / Two LCD displays / Voltage measurement up to 600V / Test leads with crocodile clips

The rotating field indicator PCE-PI 10 is used to determine the direction of rotation of 3-phase voltage networks. Furthermore, the rotating field indicator is able to measure voltages up to 600V AC / DC. The rotating field direction is important for machines and plants. If the phases are not connected correctly, damage to connected motors and pumps can occur, for example.

The rotating field indicator shows the direction of rotation on an LCD display. Furthermore, the display of the rotary field indicator shows whether a phase has been connected to the measuring lines or not. The measuring cables of the rotating field indicator are equipped with crocodile clips so that the measuring device can be connected directly to cables or screw contacts.

- 3-phase rotating field detection

- AC / DC voltage measurement
- Measuring range 75 ... 600V AC
- Test leads with crocodile clips
- CAT III 600V
- Easy handling

## **Specifications:**

Measuring range of rotating field detection 75 ... 600V AC Frequency range of rotary field recognition 40 ... 400 Hz

AC voltage AC	<b>Measuring range</b>	<b>Resolution</b>	Accuracy
	600 mV	0.1 mV	$\pm (2.3\% \text{ v.Mw} + 5 \text{ Dgt})$
	6V	1 mV	$\pm (2.3\% \text{ v.Mw} + 5 \text{ Dgt})$
	60V	10 mV	$\pm (2.3\% \text{ v.Mw} + 5 \text{ Dgt})$
	600V	0.1V	$\pm (2.3\% \text{ v.Mw} + 5 \text{ Dgt})$
DC voltage DC	600 mV 6V 60V 600V	0.1 mV 1 mV 10 mV 0.1V	$\begin{array}{l} \pm \ (0.8\% \ from + 8 \ Dgt) \\ \pm \ (0.8\% \ from + 8 \ Dgt) \\ \pm \ (0.8\% \ from + 8 \ Dgt) \\ \pm \ (0.8\% \ from + 8 \ Dgt) \\ \pm \ (0.8\% \ from + 8 \ Dgt) \end{array}$
Power supply Display Standards	2 x 1.5V AAA batt 2 x LCD displays CAT III 600V EN61010-1 EN61010-2-003 EN61326-1	tery	
Dimensions	165 x 82 x 45 mm / 6.5 x 8.2 x 1.8 in		
Weight	About 245 g / < 1 lb		

## **Delivery scope:**

1 x Digital multimeter PCE-PI 10 1 x Test lead set 2 x 1.5V AAA battery 1 x Carrying bag 1 x User manual